




2- Line, Uni-directional, Transient Voltage Suppressor



- V_{RWM} Reverse stand-off voltage
- I_R Reverse leakage current
- V_{BR} Reverse breakdown voltage
- V_C Clamping voltage
- I_{PP} Peak pulse current
- I_F Forward Current
- V_F Forward Voltage@ I_F





ESD3602E


Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	350	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	5	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	


Characteristics (Typical)



ESD3602E



Outline Dimensions





ESD3602E

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics. It is not designed for use in medical, life-saving, lifesustaining, or military applications. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

Th h Â