




- V_{DS} 60V
- I_D 5.0A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) 44mohm
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) 49mohm

- Trench Power MV MOSFET technology
- High density cell design for Low $R_{DS(ON)}$
- High Speed switching
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

- Battery protection
- Load switch
- Power management

($T_A=25$ unless otherwise noted)

Drain-source Voltage		V_{DS}	60	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_A=25\% \text{ @ Steady State}$	I_D	5.0	A
	$T_A=70\% \text{ @ Steady State}$		4.0	
	$T_A=125\% \text{ @ Steady State}$		2.2	
Pulsed Drain Current ^A		I_{DM}	25	A
Total Power Dissipation @ $T_A=25\%$		P_D	3.1	W
Thermal Resistance Junction-to-Ambient @ Steady State ^B		$R_{\theta JA}$	40.3	$^{\circ}C/W$
Avalanche energy ^C		EAS	30.25	mJ

Junction and Storage Temperature Range

T_J, T_{STG}

-55 +150


$\frac{3}{8}$ OUTER CARTON

					QUANTITY(pcs)	DELIVERY MODE
YJS05N06A	F2	Q05N06	4000	8000	64000	13" reel



■ (T_J=25 unless otherwise noted)

Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =250μA	60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V			1	μA
		V _{DS} =60V, V _{GS} =0V, T _J =125℃			100	
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D				





SYMBOL	MIN.		
	0.053	0.069	
B	0.004	0.010	
		0.061	
D		0.020	
E			
F			
G	0.050BSC		1.270BSC
H			
J			
K			
	0°		



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design