



SS22Q THRU SS24Q

Surface Mount Schottky Rectifier

Features

" /RZ SURILOH SDFNDJH
" ,GHDO IRUWDHXGWSRDFHFPHQW
" *XDUGULQJ IRU RYHUYROWDJH SURWHFWLRO
" /RZ SRZHU ORVVHV KLJK HIILF" 0HHWV 06/ 0
RI f &
" 3DUW QR ZLWKHVDQVL\$(% 4 TXDOLILHG

Typical Applications

)RU XVH LQ ORZ YROWDJH KLJK IUHTXHQF\ L
IUHHZKHHOLQJ ' &U' & FRQYHURWLYH DQG SR
SURWHFWLRO DSSOLFDWLROV

Mechanical Data

" Package '2 \$\$ 60%
0ROGLQJ FRPSRQW PHHQSODWBG33DIDBOV 06
- 67' DQG -(6' %
" Polarity: &DWKRGH OLVQWKGHRQVW

Maximum Ratings

PARAMETER	SYMBOL	UNIT	SS22Q	SS23Q	SS24Q
'HYLFH PDUNLQJ FRGH			66	66	66
5HSHWLWLYH SHDN UHYHUVH YROWDJH	V_{SD}	9			
0D[LPXP 506 YROWDJH	I_{S06}	9			
0D[LPXP ' & EORFNLQJ YROWDJH	$I_{&}$	9			
0D[LPXP DYHUDJH IRUZDUG UHFWLILHG FXUUHQW	$I_{HFWLILHG}$	DW 7	\$		
6XUJH QRQ UHSHWLWLYH IRUZDUG FXUUHQW	I_{QRQ}				
# +] KD@0•0€(23wDÄp - a					

--	--	--	--

Electrical Characteristics

PARAMETER	SYMBOL	TEST CONDITIONS	TYP	MAX	UNIT
,QVWDQWDQHRXV IRUZDUG YROWDJH			7. -		9
			7. -		
5HYHUVH FXUUHQW	I_{S5}	5DWBG 9	7. -		\$






SS22Q THRU SS24Q

Thermal Characteristics

PARAMETER	SYMBOL	UNIT	SS22Q	SS23Q	SS24Q
7KHUPDO 5HVLVWDQFH	5 . s	- :			
	5 . /				

Characteristics



Ordering Information

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SS22Q-SS24Q	)	\$SSUR[LPDWH			



SS22Q THRU SS24Q

vOutline Dimensions

DO-214AA(SMB)		
' L P	0 L Q	0 D
\$		
%		
&		
'	G™•A "É €	

y Suggested pad layout

SS22Q THRU SS24Q