

Dual PNP Small Signal Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Surface mount package ideally Suited for Automatic Insertion
- Reduces number of components and board space
- Part no. with suffix "Q" means AEC-Q101 qualified


Application

- Ideal for low power amplification and switching

Mechanical Data

- **Package:** SOT-363
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K2F

Equivalent circuit



■Maximum Ratings (Ta=25 Unless otherwise specified)

Item	Symbol	Unit	Value
Collector-Base Voltage		V	

	EBO	V	-5
Collector Current -Continuous	I _C	mA	-600
Total Device Dissipation (*)	P _D	mW	200
Thermal Resistance Junction to Ambient (*)	R _{thJA}	K/W	625
Junction Temperature	T _J		150
Storage Temperature	T _{STG}		-55 to +150

(*) Device mounted on FR-4 PCB 1.0 x 1.0 x 0.06 inch



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.