



PNP General Purpose Amplifier

Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- Low collector-emitter saturation voltage

Mechanical Data

- **Package:** SOT-89
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:**

BCX53	AH
BCX53-16	y ĩ

■Maximum Ratings (Ta=25 unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Minimum Collector-Emitter Voltage	V_{CE0}	V	$I_C = -10\text{mA}$, $I_B = 0$	-80

			$c=0$	-5
Collector Current	I_C	A		-1
Collector Power Dissipation	P_C	mW		500
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	/W		250



BCX53

■Electrical Characteristics (Ta=25 unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-Emitter Voltage	V_{CEO}	V	$I_C=-10mA, I_B=0$	-80		
Collector-Base Voltage	V_{CBO}	V	$I_C=-100\mu A, I_E=0$	-100		
Emitter-Base Voltage	V_{EBO}	V	$I_E=-100\mu A, I_C=0$	-5		
Collector-Base cut-off current	I_{CBO}	nA	$V_{CB}=-30V$			-100
	I_{EBO}		EB			
DC Current Gain	h_{FE1}		$V_{CE}=-2V, I_C=-150mA$	63		250
	h_{FE2}		$V_{CE}=-2V, I_C=-5mA$	63		
	h_{FE3}		$V_{CE}=-2V, I_C=-500mA$	40		

% & ;



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves m ww2