



DAN202

Dual Switching Diode

Features

Epoxy meets UL-94 V-0 flammability rating
Fast switching speed
High Conductance
Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

Package: SOT-23

Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

Marking: N

Maximum Rating ($T_a=25$ Unless otherwise specified)

			9 D O X H
Peak Reverse Voltage	V_{RRM}	V	80
Reverse Voltage	V_R	V	80
Forward Continuous Current	I_F	mA	100
Peak Forward Surge Current	I_{FSM}	mA	1000
Power Dissipation	P_D	mW	200
Maximum junction temperature	T_J	-	150
Storage Temperature	T_{STG}	-	-55 to +150

Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
					120000	7" reel



i



DAN202

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment rdeMd ot