




- Epoxy meets UL-94 V-0 flammability rating
- Moisure Sensitivity Level 1
- High Conductance
- Surface mount package ideally Suited for Automatic Insertion

■ (T_a=25 Unless otherwise specified)

Peak Repetitive Reverse Voltage	V _{RRM}	V	100
Reverse Voltage	V _R	V	100
Forward Continuous Current, Per Leg	I _F	mA	200
Non-Repetitive Peak Forward Surge Current @ t=8.3ms, half sine-wave	I _{FSM}	A	2
Power Dissipation	P _D	mW	350
Thermal Resistance Junction to Ambient Air	R _{θJA}	/W	357
Operation Junction Temperature	T _J		-55 to +150
Storage Temperature	T _{STG}		-55 to +150

■ (Example)

--	--	--	--

--	--	--	--	--	--	--



■ Ta=25 Unless otherwise specified, Per Leg

Reverse Voltage	V _R	V	I _R =100uA	100	
Maximum Instantaneous Forward Voltage	V _F	V	I _F =10mA, Ta=25		0.855
			I _F =100mA, Ta=25		1.2
Maximum DC Reverse Current	I _R	nA	V _R =20V		25
		uA	V _R =75V		5



■



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility.