

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

: TO-247AC

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant

: Tin plated leads, solderable per J-STD-002 and JESD22-B102

: As marked

(T_j=25 Unless otherwise specified

Device marking code			MUR3060PL
Repetitive Peak Reverse Voltage	V _{RRM}	V	30
Surge(Non-repetitive) Forward Current @60Hz half sine-wave, 1 cycle, T _a =25	I _{FSM}	A	300
Current Squared Time @1ms t 8.3ms T _j =25	I ² t	A ² s	373
Single Pulse Avalanche Energy @ T _p =40uS, T _j =25, L=15mH	E _{AS}	mJ	210
Storage Temperature	T _{stg}		-55 ~ +175
Junction Temperature	T _j		-55 ~ +175
Typical Junction capacitance @4V,1MHz	C _j	pF	160




Instantaneous forward voltage drop per diode	V_{FM}	V	$I_{FM}=30.0A @ T_j=25$	-	2.0	2.50	
			$I_{FM}=30.0A @ T_j=125$		1.65	2.0	
DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	uA	$V_{RM}=V_{RRM}$ $T_j=25$	-	-	5.0	
	I_{RRM2}		$V_{RM}=V_{RRM}$ $T_j=125$	-	-	200	
Reverse Recovery Time	T_{rr}	ns	$I_F=0.5A$ $I_{RM}=1A$ $I_{RR}=0.25A$ $T_j=25$	-	28	50	
				$T_j=25$	-	60.5	-
				$T_j=125$	-	96.98	-
Peak recovery current	I_{RRM}	A	$I_F=30A$ $di/dt=-200A/us$ $V_{RM}=400V$	$T_j=25$	-	3.53	-
				$T_j=125$	-	11.3	-
Reverse recovery charge	Q_{rr}	nC	$T_j=25$	$T_j=25$	-	106.7	-
				$T_j=125$	-	537.25	-


$T_j=25$ Unless otherwise specified

Thermal Resistance	Between junction and case	R J-C	W	1.0
	Between junction and Air	R J-A	W	50

(Typical)

3 < j e % 0





Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.11	1.36
b2	1.91	2.21
c	0.51	0.75
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.00	13.60
E2	4.80	5.20
E3	2.30	2.70
e	10.88 TYP	
L	19.62	20.22
L1	-	4.30
P	3.40	3.80

P1



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previous