



Super Fast Rectifier



Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

Mechanical Data

- **Package:** DO-201AD(DO-27)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes the cathode end


■ Maximum Ratings (Ta=25 Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR420	MUR440	MUR460	MUR480	MUR4100
Device marking code			MUR420	MUR440	MUR460	MUR480	MUR4100
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	200	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta =50	$I_{F(AV)}$	A	4.0				
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25	I_{FSM}	A	125				
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			250				
Current squared time @1ms≤t≤8.3ms Tj=25 Rating of per diode	I^2t	A ² s	65				
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	C_j	pF	60	51	45	50	
Junction Temperature	T_j		-55 ~ +150				

MUR420 THRU MUR4100



MUR420 THRU MUR4100



■ Outline Dimensions

DO-201AD(DO-27)		
Dim	Min	Max
A	8.50	9.50
B	5.00	5.60
C	25.4	/
D	1.20	1.30

