




Typical Applications

- Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-247AC
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (Tj=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	MURL3060P
Device marking code			MURL3060P
Repetitive Peak Reverse Voltage	VRRM	V	600
Average Rectified Output Current @60Hz sine wave, R-load, Tc(FIG.1)	IO	A	30
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, Tj=25	IFSM	A	300
Current Squared Time @1ms≤t≤8.3ms Tj=25	I²t	A²s	373
Storage Temperature	Tstg		-55 ~ +175
Junction Temperature	Tj		-55 ~ +175
Typical Junction capacitance @4V,1MHz	Cj	pF	197



MURL3060P

■Electrical Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V_{FM}	V	$I_{FM}=30.0A$ @ $T_j=25$	-	1.25	1.80
			$I_{FM}=30.0A$ @ $T_j=125$		1.11	1.50
DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	μA	$V_{RM}=V_{RRM}$ $T_j=25$	-	-	5.0
	I_{RRM2}		$V_{RM}=V_{RRM}$ $T_j=125$	-	-	200
Reverse Recovery Time	T_{rr}	ns	$I_F=0.5A$ $I_{RM}=1A$ $I_{RR}=0.25A$ $T_j=25$	-	40	75
			$T_j=25$	-	100	-
			$T_j=125$	-	175	-
Peak recovery current	I_{RRM}	A	$T_j=25$	-	7.50	-
			$T_j=125$	-	16.76	-
Reverse recovery charge	Q_{rr}	nC	$T_j=25$	-	375	-
			$T_j=125$	-	1450	-

■Thermal Characteristics $T_j=25$ Unless otherwise specified

PARAMETER		SYMBOL	UNIT	MURL3060P
Thermal Resistance	Between junction and case	$R_{\theta J-C}$	$^{\circ}W$	1.0
	Between junction and Air	$R_{\theta J-A}$	$^{\circ}W$	50

■ Characteristics(Typical)







FIG3: Forward Voltage





TO247-AC		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.11	1.36
b2	1.91	2.21
c	0.51	0.75
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.00	13.60
E2	4.80	5.20
E3	2.30	2.70
e	10.88 TYP	
L	19.62	20.22
L1	-	4.30
φP	3.40	3.80
φP1	-	7.30
S	6.15 TYP	



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.