



1A1G THRU 1A7G

General Purpose Rectifier

Features

- ✕ High efficiency
- ✕ High current capability
- ✕ High reliability
- ✕ High surge current capability
- ✕ Low power loss
- ✕ Glass passivated chip junction
- ✕ Solder dip 275 °C max, per JESD 22-B106

Mechanical Data

- ✕ Package: R-1
- Molding compound meets UL 94 V-0 flammability rating ,
- RoHS-compliant , Halogen free
- ✕ Terminals: Tin plated leads , solderable per J-STD-002 and JESD22-B102
- ✕ Polarity: Color band denotes cathode end

Maximum Ratings (Ta = 25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	1A1G	1A2G	1A3G	1A4G	1A5G	1A6G	1A7G
Device marking code			1A1G	1A2G	1A3G	1A4G	1A5G	1A6G	1A7G
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	400	600	800	1000
Average Forward Current @60Hz sine wave , Resistance load , Tj = 75°C	IE(AV)	A	1.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave , 1 cycle , Tj = 25°C	IFSM	A	30						
Forward Surge Current (Non-repetitive) @1ms , square wave , 1 cycle , Tj = 25°C			60						
Current squared time @1ms to 8.3ms Tj = 25°C	I²t	A²s	3.735						

UNIT

			TEST CONDITIONS	1A1G	1A2G	1A3G	1A4G	1A5G	1A6G	1A7G
Maximum instantaneous forward voltage drop per diode	VF	V	IFM = 1.0A	1.1						

Ma Å

Å a

Ba A

v7KHUPDO &KDUDÄ7WHUL8VQDHFVV RWKHUÄLVH VSHFLILHG

3\$5\$0(7(5	6<0%2/	81,7	\$ *	\$ *	\$ *	\$ *	\$ *	\$ *	\$ *
7\SLFDO 7KHUPDO	5H5LVWDQFH								

v2UGHULQJ ,QIRUPDORQ

35() (5(' 3 1	3\$&.\$*(&2' (	
---------------	-----------------	--



ΩOutline Dimensions



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronics Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability, malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices). Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes and replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> or consult your nearest Yangjie's sales office for assistance.