



1N5391GS THRU 1N5399GS

General Purpose Rectifier

Features

- " +LJK HIILFLHQF\
- " +LJK FXUUHQW FDSDELOLW\
- " +LJK UHOLDELOLW\
- " +LJK VXUJH FXUUHQW FDSDELOLW\
- " /RZ SRZHU ORVV
- " *ODVV SDVVLVDWHG FKLS MXQFWLRQ
- " 6ROGHU GLS[Y & SHDU -(6' %

Typical Applications

)RU XVH LQ JHQHUDO SIXLFD & RALRQ RI SRZHU
VXSSOLHV LQYHUWHUV FRQYHUWHUV DQG
FRQVXPHU DQG WHOHFRPPXQLFDWLRQ

Mechanical Data

- " Package '2 \$/ '2
- 0ROGLQJ FRPSRXQG PHHWV 8/ 9 IODPPDEI
- 5R+6 FRPSOLDQW
- " Terminals 7LQ SODWHG OHDGV VROGHUDEOH S
- DQG -(6' %
- " Polarity: &RORU EDQG GHQRWHV FDWKRGH HQG

Maximum Ratings 7D - 8QOHVV RWKHU 2LVH VSHFLILHG

PARAMETER	SYMBOL	UNIT	1N5391GS	1N5392GS	1N5393GS	1N5395GS	1N5397GS	1N5398GS	1N5399GS		
'HYLFH PDUNLQJ FRGH			1	*6	1	*6	1	*6	1	*6	*6
0D[LPXP 5HSHWLWLYH 3HDS 50HYHUVH 9ROWDJ											
0D[LPXP 506 9ROWDJH	9506	9									
0D[LPXP '& EORFNLQJ 9ROWDJH	9506	9									
\$YHUDJH)RUZDUG &XUUHQW # +] VLQH ZDYH 5HVLVWDQFH -		OR	DQG 7D								
)RUZDUG 6XUJH &XUUHQW # +] +DOI VLQH ZDYH - F\FOH	1RQ	UHSHWLWLYH									
)RUZDUG 6XUJH &XUUHQW # PV VTXDUH ZDYH - F\FOH	1RQ	UHSHWLWLYH									
&XUUHQW VTXDUHG WLP # PV"W "PV 7ME 5DWLQJ RI SH GLRGH											

1 * 6 7 + 5 8 1 * 6



1N5391GS THRU 1N5399GS

vOutline Dimensions

1N5391GS THRU 1N5399GS
