



- High frequency operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guaranteed O-220AB
- Soldering compound meets UL 94 V-0 flammability
- RoHS-compliant

- : Tin plated leads, solderable per J-STD-002 and JESD22-B102
- : As marked

(Ta=25 Unless otherwise specified)

| Device marking code                                                          |           |                  | MBR10200CTS |
|------------------------------------------------------------------------------|-----------|------------------|-------------|
| Repetitive Peak Reverse Voltage                                              | $V_{RRM}$ | V                | 200         |
| Average Rectified Output Current<br>@60Hz sine wave, R-load, Ta=25           | $I_O$     | A                | 10          |
| Surge(Non-repetitive)Forward Current<br>@60Hz half sine-wave, 1 cycle, Ta=25 | $I_{FSM}$ | A                | 100         |
| Current Squared Time @1ms≤t<8.3ms Tj=25                                      | $I^2t$    | A <sup>2</sup> s | 42          |
| Storage Temperature                                                          | Tstg      |                  | -55 ~ +175  |
| Junction Temperature                                                         | Tj        |                  | -55 ~ +175  |

Ta=25 Unless otherwise specified

| Maximum instantaneous forward voltage drop per diode              | $V_{FM}$   | V  | $I_{FM}=5.0A$              | 0.95 |
|-------------------------------------------------------------------|------------|----|----------------------------|------|
| Maximum DC reverse current at rated DC blocking voltage per diode | $I_{RRM1}$ | mA | $V_{RM}=V_{RRM}$<br>Ta=25  | 0.1  |
|                                                                   | $I_{RRM2}$ |    | $V_{RM}=V_{RRM}$<br>Ta=125 | 20   |

Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS



T<sub>a</sub>=25 Unless otherwise specified

|                    |                           |                   |    |     |
|--------------------|---------------------------|-------------------|----|-----|
|                    |                           |                   |    |     |
| Thermal Resistance | Between junction and case | R <sub>θJ-C</sub> | /W | 2.0 |




(Example)

|             |                 |    |      |      |      |
|-------------|-----------------|----|------|------|------|
|             |                 |    |      |      |      |
| MBR10200CTS | Approximate 1.9 | 50 | 1000 | 5000 | Tube |



(Typical)







---

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.