



Low VF Bridge Rectifiers



Features

- UL recognition, file #E230084
- based on silicon planar process
- Low VF
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** JA
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (Ta=25 Unless otherwise specified

PARAMETER		SYMBOL	UNIT	
Average Rectified Output Current @60Hz sine wave, R-load	With heatsink T _C =105	I _O	A	25.0
	Without heatsink T _a =25			4.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, T _j =25		I _{FSM}	A	360
Current squared time @1ms≤t≤8.3ms T _j =25 ,rating of per diode		I ² t	A ² S	538
Storage temperature		T _{stg}		-55 ~ +150
Junction temperature		T _j		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		V _{dis}	KV	2
Mounting torque @Recommend torque 5kg cm		T _{or}	kg cm	8



D25JAU60

■Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V_F	V	$I_{FM}=12.5A$	0.80	0.88	0.92
DC reverse current at rated DC blocking voltage per diode	I_R	μA	$T_j=25$	-	0.005	5
			$T_j=125$	-	-	50
Junction capacitance	C_j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	85	190	380

■Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER		SYMBOL	UNIT	D25JAU60
Between junction and ambient, Without heatsink		$R_{\theta J-A}$		18.0

Thermal
Resistance

/W

D25JAU60



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.