



High Efficient Bridge Rectifiers



Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

Mechanical Data

- **Package:** GBU
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings ($T_a=25$ Unless otherwise specified Å

PARAMETER		SYMBOL	UNIT	HGBU1004
Device marking code				HGBU1004
Maximum Repetitive Peak Reverse Voltage		VRRM	V	400
Maximum RMS Voltage		VRMS	V	280
Maximum DC blocking Voltage		VDC	V	400
Average rectified output current @60Hz half sine wave, R-load	With heatsink Tc =100 -	IO	A	10.0
	Without heatsink Ta =25 -			3.2
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25 -		IFSM	A	150
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25 -				300
Current squared time @1ms≤t≤8.3ms Tj=25 - , Rating of per diode		I²t	A²S	93
Storage temperature		Tstg	-	-55 ~ +150
Junction temperature		Tj	-	-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		Vdis	KV	2.5
Mounting torque @Recommend torque 0.5kg cm		Tor	kg cm	8

■Electrical Characteristics Å $T_a=25$ Unless otherwise specified Å

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	HGBU1004
-----------	--------	------	-----------------	----------

0D[LPXP UHYHUVH	UHF5YHU\	WLPH	\$5.5	\$
-----------------	----------	------	-------	----



HGBU1004

■ Thermal Characteristics $\dot{A}T_a=25$ Unless otherwise specified $\dot{A}$

PARAMETER		SYMBOL	UNIT	HGBU1004
Thermal Resistance	Between junction and ambient, Without heatsink	R θ J-A	- /W	20
	Between junction and case, With heatsink	R θ J-C		2

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
HGBU1004	B1	Approximate 3.96	20	1000	2000	TUBE

■ Characteristics (Typical)





FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions

GBU		
Dim	Min	Max
A	21.80	22.30
B	18.30	18.80
C	17.50	18.00
D	3.50	4.10
E	7.40	7.90
F	1.65	2.16
G	1.91	2.54
H	2.06	2.54
I	1.02	1.27
J	4.83	5.33
K	3.30	3.56
L	2.40	2.66
M	0.46	0.56



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.